



Full Height Turnstile

For Commercial & Industrial purpose
BX TST FH



BX TST FH 01



BX TST FH 02

Applications

- For People restricted Entry / Exit at Office / Parks / Industry / Schools

Features

- Stainless Steel # 304 body
- Bi Directional / Uni Directional
- Compatible with All Access Control
- Passenger counter (Optional)
- Direction and Lane LED Indicator
- Passenger count 25 / Min
- Protection grade IP 55
- 230V / 50 Hz / 1 W power
- Suitable for Outdoor use (with Canopy)
- It can be integrated with third party RFID/
- Biometric / Face / QR code readers

Model	BX TST FH01	BX TST FH02
AC Input Voltage	230V / 50Hz / 1 P	230V/50Hz/1PAC
Input Power	50 W	100W
Dimension	2300 H x 1500D x 1600 W mm	2300 H x 1450D x 2300 W mm
Passage Width	630 mm	620mm
Pass Speed	< 25 Person / Min	< 25 Person / Min
Box Type	Stainless Steel # 304	Stainless Steel # 304
Wings / Angle of Rotation	3 Wings / 90°	4 Wings / 90 °
Operating Condition	-15 ~ 60 Deg C	-15~60 Dec C
Humidity	< 95%	< 95%
Life Cycle (MTBF)	6 Million	6 Million

* Specification are subjected to change for improvements

